It's easy to find the perfect label with this UID Solution Supplies Selector Guide

Media & Ribbon Combination	Z-Ultimate® 4000T White with 5100 Ribbon	Z-Ultimate 4000T Silver with 5100 Ribbon	8000T Ultra High-Tack Matte with 5095 Ribbon	PolyPro™ 4000T with 5095 Ribbon	8000T Image Lock™ with Image Lock Ribbon	8000T Z-Endure™ with 5100 Ribbon	8000T Piggyback Clear Matte with 5586 Ribbon
Ribbon Type	Resin	Resin	Resin	Resin	Resin	Resin	Wax-Resin
Material description	Gloss Polyester	Gloss Polyester	Matte Polyester	Matte Polypropylene	Polyolefin	Semi-Gloss Acrylic	Gloss/Matte Polyester Combination
Adhesive types	Permanent Acrylic	Permanent Acrylic	High-Tack Permanent Acrylic	Permanent Acrylic	Permanent Acrylic	Permanent Acrylic	Permanent Acrylic
Minimum application temp.	50° F/10° C	50° F/10° C	40° F/4° C	10° F/-12° C	50° F/10° C	50° F/10° C	50° F/10° C
Service temp.	-40° F to 302° F -40° C to 150° C	-40° F to 302° F -40° C to 150° C	-20° F to 302° F -29° C to 150° C	-40° F to 250° F -40° C to 121° C	-112° F to 248° F -80° C to 120° C	-40° F to 302° F -40° C to 150° C	-40° F to 302° F -40° C to 150° C
Surface to be labeled	Corrugate, Paper, Packaging Films, Metal, Glass	Corrugate, Paper, Packaging Films, Metal, Glass	Corrugate, Paper, Packaging Films, Metal, Glass, Rough Surfaces	Corrugate, Paper, Packaging Films, Metal, Glass	Corrugate, Paper, Packaging Films, Metal, Glass, Curved Surfaces	Corrugate, Paper, Packaging Films, Metal, Glass	Corrugate, Paper, Packaging Films, Metal, Glass
Environment	Indoor Outdoor up to 3 years	Indoor Outdoor up to 3 years	Indoor Outdoor up to 3 years	Indoor Outdoor up to 2 years	Indoor Outdoor up to 5 years	Indoor Outdoor up to 10 years	Indoor Outdoor up to 3 years
Resistance	Moisture, Abrasion, Weak-to-Moderate Chemicals	Moisture, Abrasion, Weak-to-Moderate Chemicals	Moisture, Weak-to-Moderate Chemicals	Moisture, Weak-to-Harsh Chemicals	Moisture, Abrasion, Weak-to-Harsh Chemicals	Moisture, Abrasion, Weak-to-Moderate Chemicals	Moisture, Abrasion, Weak-to-Harsh Chemicals
Compliant to MIL-PRF-61002A	Type II, Grade A B & C, Style 1, Composition b	Type II, Grade A B & C, Style 1, Composition b	Type II, Grade A B & C, Style 1, Composition b	Type II, Grade A B & C, Style 1, Composition b	Type II, Grade A B & C, Style 1, Composition b	Type II, Grade A B & C, Style 1, Composition b	Type II, Grade A B & C, Style 1, Composition b